

CITY of STERLING HEIGHTS
SOIL EROSION AND SEDIMENTATION CONTROL

GENERAL

1. All erosion and sediment control work shall conform to the standards and specifications of the City of Sterling Heights.
2. Daily inspections shall be made by the contractor to determine effectiveness of erosion and sedimentation control measures and any necessary repairs shall be performed without delay.
3. Erosion and any sedimentation from work on this site shall be contained on the site and not allowed to collect on any off-site areas or in waterways. Waterways include both natural and man-made open ditches, streams, storm drains, lakes and ponds.
4. Erosion and sedimentation control measures are to be placed prior to or as the first step in construction. Sedimentation control practices shall be applied as a perimeter defense against any transporting of silt or soils off the site.
5. Contractor shall apply temporary erosion and sedimentation control measures as required and as directed on these plans. He shall remove temporary measures as soon as permanent stabilization of slopes, ditches, and other earth changes have been accomplished.
6. Permanent soil erosion control measures for all slopes, channels, ditches, or any disturbed lawn area shall be completed within 5 calendar days after final grading or the final earth change has been completed. When it is not possible to stabilize a disturbed area after the earth change has been completed, or where significant earth change activity has ceased, temporary soil erosion control measures shall be implemented for 30 calendar days. All permanent soil erosion control measures will be implemented and established before a certificate of compliance is issued.
7. All mud/dirt tracked onto existing city/county/state roads from this site due to construction shall be removed by the contractor/builder at the end of the work day or immediately if a driving hazard is present.

All mud/dirt tracked or spilled on paved roads/surfaces within this site shall be promptly removed by the contractor/builder.

8. All onsite and off-site areas disturbed by construction shall be restored to equal or better than original existing conditions. All restoration shall consist of a minimum of 3" of topsoil with seed and mulch or 3" of topsoil and Class "A" sod where existing condition require sod replacement.